



CIRCUIT: SPDT  
CONTACT CONFIGURATION

SWITCH FUNCTION		
PDS. 1	PDS. 2	PDS. 3
DN	NONE	DN
2-3	DPEN	2-1

- NOTES:
1. ALL DIMENSIONS IN MM [INCH]
  2. GENERAL TOLERANCE: 0.0=±0.4  
0.00=±0.25
  3. TERM. NOS. FOR REF. ONLY
  4. RATING: 3 Amps @120 VAC or 28 VDC; 1.5 Amps @250 VAC.
  5. ELECTRICAL LIFE: 30,000 make-and-break cycles at full load.
  6. INSULATION RESISTANCE: 1000 mega-ohm typical
  7. DIELECTRIC STRENGTH: 1,000 V RMS @sea level
  8. OPERATING TEMP.: -30°C to 85°C



A	10740	RELEASED FOR PRODUCTION	7/7/00	MM
REV.	ECN No.	DESCRIPTION	DATE	CHKD

TITLE		SCALE	DATE	DR	DWG	REV
400A WMSP-1 R1 M7 Q E		2:1	7/7/00	MM	T402999	A

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED