







## 61CNQ SERIES SCHOTTKY RECTIFIER

### Applications

- Switching power supply
- Converters
- Free-Wheeling diodes
- Reverse battery protection

### Features

- 175°C T<sub>J</sub> operation
- Center tap module
- Very Low forward voltage drop
- High purity, high temperature epoxy encapsulation for enhanced mechanical strength and moisture resistance
- High frequency operation
- Guard ring for enhanced ruggedness and long term reliability
- Low profile, high current package
- This is a Pb – Free Device
- All SMC parts are traceable to the wafer lot
- Additional electrical and life testing can be performed upon request

61CNQ...	61CNQ...SL	61CNQ...SM
		
		
<b>PRM3</b>	<b>PRM3-SL</b>	<b>PRM3-SM</b>

### Maximum Ratings:

Characteristics	Symbol	Condition	Max.	Units
Peak Repetitive Reverse Voltage Working Peak Reverse Voltage DC Blocking Voltage	V <sub>RRM</sub> V <sub>RWM</sub> V <sub>R</sub>	-	35(61CNQ035) 40(61CNQ040) 45(61CNQ045)	V
Average Rectified Forward Current	I <sub>F (AV)</sub>	50% duty cycle @T <sub>C</sub> =149°C, rectangular wave form	30(Per Leg) 60(Per Device)	A
Peak One Cycle Non-Repetitive Surge Current(Per leg)	I <sub>FSM</sub>	8.3 ms, half Sine pulse	990	A
Non-Repetitive Avalanche Energy (Per leg)	E <sub>AS</sub>	T <sub>J</sub> =25°C, I <sub>AS</sub> =6A, L=2.2mH	40	mJ
Repetitive Avalanche Current(Per leg)	I <sub>AR</sub>	Current decaying linearly to zero in 1 μsec Frequency limited by T <sub>J</sub> max. V <sub>A</sub> =1.5×V <sub>R</sub> typical	6	A

**Electrical Characteristics:**

Characteristics	Symbol	Condition	Typ.	Max.	Units
Forward Voltage Drop (Per leg) *	V <sub>F1</sub>	@ 30A, Pulse, T <sub>J</sub> = 25 °C	0.51	0.61	V
		@ 60A, Pulse, T <sub>J</sub> = 25 °C	0.56	0.68	
	V <sub>F2</sub>	@ 30A, Pulse, T <sub>J</sub> = 125 °C	0.43	0.49	V
		@ 60A, Pulse, T <sub>J</sub> = 125 °C	0.50	0.60	
Reverse Current (Per leg) *	I <sub>R1</sub>	@V <sub>R</sub> = rated V <sub>R</sub> , T <sub>J</sub> = 25 °C	0.03	5	mA
	I <sub>R2</sub>	@V <sub>R</sub> = rated V <sub>R</sub> , T <sub>J</sub> = 125 °C	25	45	mA
Junction Capacitance (Per leg)	C <sub>T</sub>	@V <sub>R</sub> = 5V, T <sub>C</sub> = 25 °C f <sub>SIG</sub> = 1MHz	2300	2600	pF
Series Inductance (Per leg)	L <sub>S</sub>	Measured lead to lead 5 mm from package body	6.0	-	nH
Voltage Rate of Change	dv/dt	-	-	10,000	V/μs


\* Pulse width < 300 μs, duty cycle < 2%

**Thermal-Mechanical Specifications:**


Characteristics	Symbol	Condition	Specification	Units
Junction Temperature	T <sub>J</sub>	-	-55 to +175	°C
Storage Temperature	T <sub>stg</sub>	-	-55 to +175	°C
Typical Thermal Resistance Junction to Case (per leg)	R <sub>θJC</sub>	DC operation	0.85	°C/W
Typical Thermal Resistance Junction to Case (per package)	R <sub>θJC</sub>	DC operation	0.42	°C/W
Typical Thermal Resistance, case to Heat Sink	R <sub>θcs</sub>	Mounting surface, smooth and greased	0.30	°C/W
Mounting Torque	TM	-	40(min)	Kg-cm
			58(max)	
Approximate Weight	wt	-	7.8	g
Case Style	PRM3 PRM3-SL PRM3-SM			

**Ratings and Characteristics Curves**


**Typical Forward Characteristics**




**Typical Reverse Characteristics**



**Typical Junction Capacitance**



**Marking Diagram**



Where XXXX is YYWW


1st row SS YYWWL  
2nd row 61CNQ035/SL/SM  
3rd row 1 2 3 (pin)  
SS = SS  
YY = Year  
WW = Week

**Cautions:** Molding resin  
Epoxy resin UL:94V-0


**Ordering Information**

Device	Package	Terminals finish	Shipping
61CNQ035	PRM3	Nickel plated	48pcs / box
61CNQ035S	PRM3	Pure Sn dipped (dipped height 6-8 mm)	48pcs / box
61CNQ040	PRM3	Nickel plated	48pcs / box
61CNQ040S	PRM3	Pure Sn dipped (dipped height 6-8 mm)	48pcs / box
61CNQ045	PRM3	Nickel plated	48pcs / box
61CNQ035SL	PRM3-SL	Nickel plated	100pcs / box
61CNQ040SL	PRM3-SL	Nickel plated	100pcs / box
61CNQ045SL	PRM3-SL	Nickel plated	100pcs / box
61CNQ035SM	PRM3-SM	Nickel plated	48pcs / box
61CNQ040SM	PRM3-SM	Nickel plated	48pcs / box
61CNQ045SM	PRM3-SM	Nickel plated	48pcs / box


**Mechanical Dimensions PRM3 (Inches/Millimeters)**



**Mechanical Dimensions PRM3-SL (Inches/Millimeters)**



**Mechanical Dimensions PRM3-SM (Inches/Millimeters)**





**DISCLAIMER:**

1- The information given herein, including the specifications and dimensions, is subject to change without prior notice to improve product characteristics. Before ordering, purchasers are advised to contact the SMC - Sangdest Microelectronics (Nanjing) Co., Ltd sales department for the latest version of the datasheet(s).

2- In cases where extremely high reliability is required (such as use in nuclear power control, aerospace and aviation, traffic equipment, medical equipment, and safety equipment), safety should be ensured by using semiconductor devices that feature assured safety or by means of users' fail-safe precautions or other arrangement.

3- In no event shall SMC - Sangdest Microelectronics (Nanjing) Co., Ltd be liable for any damages that may result from an accident or any other cause during operation of the user's units according to the datasheet(s). SMC - Sangdest Microelectronics (Nanjing) Co., Ltd assumes no responsibility for any intellectual property claims or any other problems that may result from applications of information, products or circuits described in the datasheets.

4- In no event shall SMC - Sangdest Microelectronics (Nanjing) Co., Ltd be liable for any failure in a semiconductor device or any secondary damage resulting from use at a value exceeding the absolute maximum rating.

5- No license is granted by the datasheet(s) under any patents or other rights of any third party or SMC - Sangdest Microelectronics (Nanjing) Co., Ltd.

6- The datasheet(s) may not be reproduced or duplicated, in any form, in whole or part, without the expressed written permission of SMC - Sangdest Microelectronics (Nanjing) Co., Ltd.

7- The products (technologies) described in the datasheet(s) are not to be provided to any party whose purpose in their application will hinder maintenance of international peace and safety nor are they to be applied to that purpose by their direct purchasers or any third party. When exporting these products (technologies), the necessary procedures are to be taken in accordance with related laws and regulations..